




FILLED CELL DIMENSIONS ARE LOCATED FROM PLANS PROVIDED. DOOR & WINDOW OPENINGS SHALL BE COORDINATED WITH SPECIFIC MANUFACTURER.



**FOUNDATION LEGEND**

SYMBOL	DESIGN DESCRIPTION
■	INDICATES FILLED CELL w/3000 PSI CONCRETE CONSTRUCTED PER DETAIL MS01/SN AND SPACED PER PLAN
□	INDICATES FILLED CELL BELOW WINDOWS w/3000 PSI CONCRETE CONSTRUCTED PER DETAIL MS01/SN AND SPACED PER PLAN
F#.#	INDICATES CONCRETE FOOTING w/ MINIMUM SOIL BEARING CAPACITY OF 2000 PSF. REINFORCE PER GENERAL FOUNDATIONS SCHEDULE ON SHEET SN FOR DESIGN SPECIFICATIONS.
▨	INDICATES CONSTRUCTION JOINT (IF SHOWN) SHALL BE 1/2" x 1" SAW CUTS FILLED WITH APPROVED SLAB JOINT MATERIAL COVERING A 12x12' SQUARE MAXIMUM
▧	INDICATES STEP IN FOUNDATION, VERIFY PER ARCHITECTURAL PLANS CONSTRUCT PER PLAN SECTION CUT AND DETAIL SHEET D1
0'-0" FIN. FLR.	4" 2500 PSI CONC. SLAB W/ REINF. PER S0 w/6 MIL VISQUEEN VAPOR BARRIER & TREATED FOR TERMITES. SEE FOUNDATION SCHEDULE ON SN
▩	INDICATES BUILT UP COLUMN, SEE FRAMING PLAN FOR SIZE, DETAIL WF37/SN FOR PLY ATTACHMENT, AND UPLIFT CONNECTION SCHEDULE ON SN FOR CONNECTION TO SLAB

GENERAL NOTES:  
 1. TYPICAL CORNER FRAMING PER DETAIL FM19/D1  
 2. SEE ARCHITECTURAL PLANS FOR ALL SLAB STEP DEPTHS IF SHOWN WITHIN THESE DOCUMENTS.

FILLED CELL NOTES:  
 1. SEE PLAN FOR ZONE MIDDLE AND END DESIGNATIONS  
 2. PLACE FILLED CELLS AT ALL BUILDING CORNER, UNDER GIRDERS, BOTH ENDS OF EXTERIOR WALL OPENING, AND WHERE INTERIOR BEARING WALLS ARE PERPENDICULAR TO EXTERIOR MASONRY WALL.  
 3. PLACE 1-#5 IN FIRST TWO CELLS ADJACENT TO GARAGE DOOR OPENING & ALL OPENINGS 8'-0" & LARGER. FILL CELLS SOLID.  
 4. PLACE 1-#5 WHERE WOOD BEAMS CONNECT TO MASONRY WALL  
 5. NO NOT PLACE FILLED CELLS DIRECTLY IN LINE w/ STOVE VENT


**PLAN KEY NOTES**

- 1 12" x 12" CMU COL. w/ (2) #5 - T/COL. EL. 9'-4" A.F.F.

BUILDER NOTE:  
 ANY DISCREPANCY OR ERROR IN DIMENSIONS OR NOTES SHALL BE BROUGHT TO THE ATTENTION OF THE DESIGN PROFESSIONAL FOR CLARIFICATION PRIOR TO COMMENCEMENT OF CONSTRUCTION

**WALL TYPE**

SYMBOL	DESIGN DESCRIPTION
▨	2x INTERIOR BEARING SHEARWALL - SEE BEARING WALL SCHEDULE ON SHEET SN FOR REQUIREMENTS.
▩	INDICATES BEARING WALL SEE BEARING WOOD BEARING SCHEDULE ON SN
▧	MASONRY WALL TOP @ 9'-4"
▨	MASONRY WALL TOP @ 10'-8" ABV. GRADE
▩	MASONRY WALL TOP @ 10'-8" ABV. GRADE



**FOUNDATION PLAN**  
 SCALE: 1/4" = 1'-0"

**B&A Design Studio, Inc.**  
 4017 W. 1st Street  
 Sanford, FL 32771  
 PH: 407 839 8900  
 FAX: 407 839 2040  
 www.badesignstudios.com

**Professional Engineer**  
 CARL A. BROWN, PE, FL #9226  
 SCOTT LEWIS, PE, FL #9790  
 DATE: November 9, 2023

**Professional Engineer**  
 CARL A. BROWN, PE, FL #9226  
 SCOTT LEWIS, PE, FL #9790  
 DATE: November 9, 2023

**FDS ENGINEERING ASSOCIATES**  
 288 Southhall Lane, Suite 200, Maitland, FL 32751  
 Phone: 407-839-8900  
 Fax: 407-839-2040  
 www.fdseng.com


**FDS JOB NO.:**  
 2023083

**PARK SQUARE HORIZONS WEST**  
 BABCOCK RANCH BLDG. (LOTS 1-4) UNIT

title:  
 project no. 2023083  
 checked: BA  
 drawn: BA  
 date: 04-12-23  
 scale:  
**S1.1**

NOTE: DRAWINGS ON 11"x17" SHEET WILL BE ONE HALF THE SCALE NOTED

FILLED CELL DIMENSIONS ARE LOCATED FROM PLANS PROVIDED. DOOR & WINDOW OPENINGS SHALL BE COORDINATED WITH SPECIFIC MANUFACTURER.



### FOUNDATION LEGEND

SYMBOL	DESIGN DESCRIPTION
■	INDICATES FILLED CELL w/3000 PSI CONCRETE CONSTRUCTED PER DETAIL MS01/SN AND SPACED PER PLAN
□	INDICATES FILLED CELL BELOW WINDOWS w/3000 PSI CONCRETE CONSTRUCTED PER DETAIL MS01/SN AND SPACED PER PLAN
F#	INDICATES CONCRETE FOOTING w/ MINIMUM SOIL BEARING CAPACITY OF 2000 PSF. REINFORCE PER GENERAL FOUNDATIONS SCHEDULE ON SHEET SN FOR DESIGN SPECIFICATIONS.
J	INDICATES CONSTRUCTION JOINT (IF SHOWN) SHALL BE 1/2" x 1" SAW CUTS FILLED WITH APPROVED SLAB JOINT MATERIAL COVERING A 12"x12" SQUARE MAXIMUM
≡	INDICATES STEP IN FOUNDATION. VERIFY PER ARCHITECTURAL PLANS CONSTRUCT PER PLAN SECTION CUT AND DETAIL SHEET D1
0'-0" FIN. FLR.	4" 2500 PSI CONC. SLAB W/ REINF. PER S0 w/6 MIL VISQUEEN VAPOR BARRIER & TREATED FOR TERMITES. SEE FOUNDATION SCHEDULE ON SN
▨	INDICATES BUILT UP COLUMN. SEE FRAMING PLAN FOR SIZE, DETAIL WF37/SN FOR PLY ATTACHMENT, AND UPLIFT CONNECTION SCHEDULE ON SN FOR CONNECTION TO SLAB

GENERAL NOTES:  
 1. TYPICAL CORNER FRAMING PER DETAIL FM19/D1  
 2. SEE ARCHITECTURAL PLANS FOR ALL SLAB STEP DEPTHS IF SHOWN WITHIN THESE DOCUMENTS.

FILLED CELL NOTES:  
 1. SEE PLAN FOR ZONE MIDDLE AND END DESIGNATIONS  
 2. PLACE FILLED CELLS AT ALL BUILDING CORNER, UNDER GIRDERS, BOTH ENDS OF EXTERIOR WALL OPENING, AND WHERE INTERIOR BEARING WALLS ARE PERPENDICULAR TO EXTERIOR MASONRY WALL.  
 3. PLACE 1-#5 IN FIRST TWO CELLS ADJACENT TO GARAGE DOOR OPENING & ALL OPENINGS 8'-0" & LARGER. FILL CELLS SOLID.  
 4. PLACE 1-#5 WHERE WOOD BEAMS CONNECT TO MASONRY WALL  
 5. NO NOT PLACE FILLED CELLS DIRECTLY IN LINE w/ STOVE VENT


### PLAN KEY NOTES

SEE FOUNDATION LEGEND

**BUILDER NOTE:**  
 ANY DISCREPANCY OR ERROR IN DIMENSIONS OR NOTES SHALL BE BROUGHT TO THE ATTENTION OF THE DESIGN PROFESSIONAL FOR CLARIFICATION PRIOR TO COMMENCEMENT OF CONSTRUCTION

### WALL TYPE

SYMBOL	DESIGN DESCRIPTION
▨	2x INTERIOR BEARING SHEARWALL - SEE BEARING WALL SCHEDULE ON SHEET SN FOR REQUIREMENTS.
▨	INDICATES BEARING WALL SEE BEARING WOOD BEARING SCHEDULE ON SN
▨	MASONRY WALL TOP @ 9'-4"
▨	MASONRY WALL TOP @ 10'-8" ABV. GRADE
▨	MASONRY WALL TOP @ 10'-8" ABV. GRADE



**FOUNDATION PLAN**  
 SCALE: 1/4" = 1'-0"

**B&A Design Studio, Inc.**  
 4017 W. 1st Street  
 Sanford, FL 32771  
 ph: 407 829 8900  
 fax: 407 829 2040  
 www.badesignstudios.com

**AI AMERICAN INSTITUTE OF ARCHITECTS**  
 N.C.B.D.O. REGISTERED ARCHITECT


**FDS ENGINEERING ASSOCIATES**  
 288 Southhall Lane, Suite 200, Maitland, FL 32751  
 (407) 829-8900  
 Certificate of Authorization No. 9191  
 □ CARL A. BROWN, PE, FL # 45626  
 □ SCOTT LEWIS, PE, FL # 27970  
 DATE: November 9, 2023  
 THE SEAL OF THE PROFESSIONAL ENGINEER IS THE PROPERTY OF THE BOARD OF PROFESSIONAL ENGINEERS AND SURVEYORS OF THE STATE OF FLORIDA. IT IS TO BE USED ONLY BY THE ENGINEER FOR THE PROJECT AND FOR THE PERIOD OF TIME SPECIFIED ON THE SEAL.


**FDS**  
 FDS JOB NO.: \_\_\_\_\_

**PARK SQUARE  
 HORIZONS WEST  
 BABCOCK RANCH BLDG. (LOTS 1-4) UNIT**

title: \_\_\_\_\_  
 project no. 2023083  
 checked: \_\_\_\_\_  
 drawn: BA  
 date: 04-12-23  
 scale: \_\_\_\_\_  
**S1.2**

NOTE: DRAWINGS ON 11"x17" SHEET WILL BE ONE HALF THE SCALE NOTED

<b>RSH</b>	ENGINEERED ROOF PER ASCE 7-16 ROOF DESIGN ALLOWABLE COMPONENTS AND CLADDING WIND PRESSURES AND SUCTIONS FOR MEAN ROOF HEIGHT ≤ 25 ft
WIND SPEED (ULTIMATE)	150.0 MPH
WIND SPEED (ALLOWABLE)	116.2 MPH
EXPOSURE CATEGORY	C
EFFECTIVE WIND AREA (SQ FEET)	WIND PRESSURE AND SUCTION (PSF) (+) VALUE DENOTES PRESSURE (-) VALUE DENOTES SUCTION
AREA	ROOF 1 2e 2n 2r 3 3e 3r
10	HIP -43.90 -60.59 -60.59 -60.59 -60.59 GABLE -43.86 -43.86 -69.97 -69.97 -69.97 -90.23
ROOF NAILING SCHEDULE/ NAILING ZONES (SHINGLE AND TILE):	
ZONE 1: ASTM F1667 RSR-01 (8d) NAILS @ 6" O.C. ON EDGE AND 6" O.C. IN FIELD	
ZONE 2e, 2n, 2r: ASTM F1667 RSR-01 (8d) NAILS @ 4" O.C. ON EDGE AND 4" O.C. IN FIELD	
ZONE 3, 3e, 3r: ASTM F1667 RSR-01 (8d) NAILS @ 4" O.C. ON EDGE AND 4" O.C. IN FIELD	
ROOF SHEATHING: SHINGLE: 7/8" EXP. 1 (2%) or 1 1/2" EXP. 1 (2%)	
TILE: 1 1/2" EXP. 1 (2%)	
NOTE: 1. PER CODE ASTM F1667 RSR-01 REFERENCE TO 8d (2 1/4" x 0.113") NAILS 2. WHERE THE SHEATHING THICKNESS IS GREATER THAN 1/2", SHEATHING SHALL BE FASTENED WITH ASTM F1667 RSR-03 10d (2 1/2" x 0.131") NAILS OR ASTM F1667 RSR-04 (3" x 120") NAILS 3. GABLES- DROP GABLE END & (1) ADDITIONAL DROPPED TRUSS 2x4 #2 SYP OUTLOOKER RAFTER W/ BLOCKING @ 16" O.C. IF NO DROPPED GABLE END. ATTACH 2x4 #2 SYP BLOCKING @ 16" O.C. FIRST 4 BAYS WITH (2) 12d NAILS EA. END. ATTACH ROOF SHEATHING TO RAFTERS W/ BLOCKING PER NAILING SCHEDULE.	
HIP ROOF > 20 TO 27 DEG. [4-12]-[6-12]	
	
GABLE ROOF > 20 TO 27 DEG. [4-12]-[6-12]	



SYMBOL	DESIGN DESCRIPTION
	INDICATES BEARING WALL SEE BEARING WOOD BEARING SCHEDULE ON SN, SEE ARCHITECTURAL PLANS FOR WALL WIDTH, 2x4 MINIMUM U.O.N.
	INDICATES PERFORATED SHEAR WALL, SEE ARCHITECTURAL PLANS FOR WALL WIDTH, 2x4 MINIMUM U.O.N.
	INDICATES BUILT UP COLUMN, SEE FRAMING PLAN FOR SIZE, DETAIL WF37/SN FOR PLY ATTACHMENT AND UPLIFT CONNECTION SCHEDULE ON SN FOR CONNECTION TO SLAB
	INDICATES NO BOTTOM CONNECTOR REQUIRED
	INDICATES UPLIFT CONNECTION CONSTRUCTED PER DETAIL UPLIFT CONNECTOR SCHEDULE ON SHEET SN
	INDICATES WINDOW PRESSURE - SEE S0 FOR MORE INFORMATION.
	INDICATES LINTEL PER LINTEL PLAN


- FRAMING NOTES:**
- SEE WIND SPEED CHART ON S0 FOR WINDOW PRESSURES
  - AT SECOND FLOOR FOR TYPICAL CORNER FRAMING SEE DETAIL FB06/D3
- GENERAL NOTES:**
- THE FRAMING PLAN SHOWN INDICATES THE "TRUSS SYSTEM" AND IS THE RESPONSIBILITY OF THE TRUSS SYSTEM ENGINEER (DESIGN PROFESSIONAL OF RECORD), THE TRUSS DESIGN ENGINEER (DELEGATED ENGINEER) HAS FINAL, RESPONSIBILITY FOR EACH INDIVIDUAL TRUSS AND TRUSS PROFILE, AND IS TO SUBMIT A FINAL SET OF TRUSS ENGINEERING SIGNED AND SEALED TRUSS DRAWINGS TO DESIGN PROFESSIONAL OF RECORD FOR REVIEW PRIOR TO FABRICATION
  - ANY DISCREPANCY OR ERROR IN DIMENSIONS OR NOTES WITH IN THIS PLAN SHALL BE BROUGHT TO THE ATTENTION OF THE DESIGN PROFESSIONAL FOR CLARIFICATION PRIOR TO CONSTRUCTION.
  - SEE SHEET SN FOR DESIGN SCHEDULES AND NOTES: FOUNDATION SCHEDULE / COLUMN SCHEDULE / BEARING WALL SCHEDULE / BEAM SCHEDULE / HEADER SCHEDULE / CONNECTION SCHEDULE / FLOOR AND ROOF NOTES.

- PLAN KEY NOTES**
- 12" SQ CMU COLUMN W/ (2) #5 FULLY GROUTED
  - LGUM28-3-SDS CONNECTOR BY SIMPSON STRONG TIE W/ (6) 3/8"x4" TITEN HD ANCHORS TO MASONRY AND (6) 1/4"x2-1/2" STRONG DRIVE SDS SCREWS

**BUILDER NOTE:**  
TRUSS LAYOUT, CONNECTORS & ENGINEERING BASED ON TRUSSES PROVIDED BY A-1 INDUSTRIES. PROJECT NAME CPSMU4 w/ TRUSS DESIGN DATED 4/24/23 IF THE TRUSS LAYOUT SHOWN DOES NOT MATCH THE TRUSS MANUFACTURERS LAYOUT AND DATE ABOVE

**STOP**  
AND CALL THE ENGINEER OF RECORD PRIOR TO PLACEMENT OF ANY TRUSSES.

SYMBOL	DESIGN DESCRIPTION
	2x INTERIOR BEARING SHEAR WALL - SEE BEARING WALL SCHEDULE ON SHEET SN FOR REQUIREMENTS.
	INDICATES BEARING WALL SEE BEARING WOOD BEARING SCHEDULE ON SN
	MASONRY WALL TOP @ 9'-4"
	MASONRY WALL TOP @ 10'-8" ABV. GRADE
	MASONRY WALL TOP @ 10'-8" ABV. GRADE



**KEY PLAN**  
**LOW ROOF & FLOOR FRAMING PLAN**  
SCALE: 1/4" = 1'-0"

**B&A Design Studio, Inc.**  
4017 W. 1st Street  
Sanford, FL 32771  
PH: 407 829 8900  
FAX: 407 829 2040  
www.badesignstudios.com

**A.I. AMERICAN INSTITUTE OF DESIGN**  
N.C.B.D.O.  
Professional Engineer License No. 9161  
Professional Engineer License No. 9162  
Professional Engineer License No. 9163  
Professional Engineer License No. 9164  
Professional Engineer License No. 9165  
Professional Engineer License No. 9166  
Professional Engineer License No. 9167  
Professional Engineer License No. 9168  
Professional Engineer License No. 9169  
Professional Engineer License No. 9170

**FDS ENGINEERING ASSOCIATES**  
288 Southhall Lane, Suite 200, Maitland, FL 32751  
Professional Engineer License No. 9161  
Professional Engineer License No. 9162  
Professional Engineer License No. 9163  
Professional Engineer License No. 9164  
Professional Engineer License No. 9165  
Professional Engineer License No. 9166  
Professional Engineer License No. 9167  
Professional Engineer License No. 9168  
Professional Engineer License No. 9169  
Professional Engineer License No. 9170


**PARK SQUARE HORIZONS WEST**  
BABCOCK RANCH BLDG. (LOTS 1-4) UNIT

title:  
project no. 2023083  
checked:  
drawn: BA  
date: 04-12-23  
scale:  
**S2.1**

The structural design of this building is in accordance with the FLORIDA BUILDING CODE 7TH EDITION (2020) RESIDENTIAL and is certified as such.

NOTE: DRAWINGS ON 11"x17" SHEET WILL BE ONE HALF THE SCALE NOTED

<b>RSH</b>	ENGINEERED ROOF PER ASCE 7-16 ROOF DESIGN ALLOWABLE COMPONENTS AND CLADDING WIND PRESSURES AND SUCTIONS FOR MEAN ROOF HEIGHT ≤ 25 ft							
WIND SPEED (ULTIMATE)	150.0 MPH							
WIND SPEED (ALLOWABLE)	116.2 MPH							
EXPOSURE CATEGORY	C							
EFFECTIVE WIND AREA (SQ FEET)	WIND PRESSURE AND SUCTION (PSF) (+) VALUE DENOTES PRESSURE (-) VALUE DENOTES SUCTION							
AREA	ROOF	1	2a	2n	2r	3	3a	3r
10	HIP	-43.90	-60.59	-60.59	-60.59	-60.59		
	GABLE	-43.86	-43.86	-69.97	-69.97	-69.97	-69.97	-90.23
ROOF NAILING SCHEDULE/ NAILING ZONES (SHINGLE AND TILE):								
ZONE 1: ASTM F1667 RSR-01 (8d) NAILS @ 6" O.C. ON EDGE AND 6" O.C. IN FIELD								
ZONE 2a, 2n, 2r: ASTM F1667 RSR-01 (8d) NAILS @ 4" O.C. ON EDGE AND 4" O.C. IN FIELD								
ZONE 3, 3a, 3r: ASTM F1667 RSR-01 (8d) NAILS @ 4" O.C. ON EDGE AND 4" O.C. IN FIELD								
ROOF SHEATHING: SHINGLE: 7/8" EXP. 1 (2%) or 1 1/2" EXP. 1 (2%)								
TILE: 1 1/2" EXP. 1 (2%)								
NOTE: 1. PER CODE ASTM F1667 RSR-01 REFERENCE TO 8d (2 1/4" x 0.113") NAILS 2. WHERE THE SHEATHING THICKNESS IS GREATER THAN 1/2", SHEATHING SHALL BE FASTENED WITH ASTM F1667 RSR-03 10d (2 1/2" x 0.131") NAILS OR ASTM F1667 RSR-04 (3" x 120") NAILS 3. GABLES- DROP GABLE END & (1) ADDITIONAL DROPPED TRUSS 2x4 #2 SYP OUTLOOKER RAFTER W/ BLOCKING @ 16" O.C. IF NO DROPPED GABLE END. ATTACH 2x4 #2 SYP BLOCKING @ 16" O.C. FIRST 4 BAYS WITH (2) 12d NAILS EA. END. ATTACH ROOF SHEATHING TO RAFTERS W/ BLOCKING PER NAILING SCHEDULE.								
HIP ROOF > 20 TO 27 DEG. [4-12]-[6-12]								
GABLE ROOF > 20 TO 27 DEG. [4-12]-[6-12]								



SYMBOL	DESIGN DESCRIPTION
	INDICATES BEARING WALL SEE BEARING WOOD BEARING SCHEDULE ON SN, SEE ARCHITECTURAL PLANS FOR WALL WIDTH, 2x4 MINIMUM U.O.N.
	INDICATES PERFORATED SHEAR WALL, SEE ARCHITECTURAL PLANS FOR WALL WIDTH, 2x4 MINIMUM U.O.N.
	INDICATES BUILT UP COLUMN, SEE FRAMING PLAN FOR SIZE, DETAIL WF37/SN FOR PLY ATTACHMENT AND UPLIFT CONNECTION SCHEDULE ON SN FOR CONNECTION TO SLAB
	INDICATES NO BOTTOM CONNECTOR REQUIRED
	INDICATES UPLIFT CONNECTION CONSTRUCTED PER DETAIL UPLIFT CONNECTOR SCHEDULE ON SHEET SN
	INDICATES WINDOW PRESSURE - SEE S0 FOR MORE INFORMATION.
	INDICATES LINTEL PER LINTEL PLAN


- FRAMING NOTES:**
- SEE WIND SPEED CHART ON S0 FOR WINDOW PRESSURES
  - AT SECOND FLOOR FOR TYPICAL CORNER FRAMING SEE DETAIL FB06/D3
- GENERAL NOTES:**
- THE FRAMING PLAN SHOWN INDICATES THE "TRUSS SYSTEM" AND IS THE RESPONSIBILITY OF THE TRUSS SYSTEM ENGINEER (DESIGN PROFESSIONAL OF RECORD), THE TRUSS DESIGN ENGINEER (DELEGATED ENGINEER) HAS FINAL, RESPONSIBILITY FOR EACH INDIVIDUAL TRUSS AND TRUSS PROFILE, AND IS TO SUBMIT A FINAL SET OF TRUSS ENGINEERING SIGNED AND SEALED TRUSS DRAWINGS TO DESIGN PROFESSIONAL OF RECORD FOR REVIEW PRIOR TO FABRICATION
  - ANY DISCREPANCY OR ERROR IN DIMENSIONS OR NOTES WITH IN THIS PLAN SHALL BE BROUGHT TO THE ATTENTION OF THE DESIGN PROFESSIONAL FOR CLARIFICATION PRIOR TO CONSTRUCTION.
  - SEE SHEET SN FOR DESIGN SCHEDULES AND NOTES: FOUNDATION SCHEDULE / COLUMN SCHEDULE / BEARING WALL SCHEDULE / BEAM SCHEDULE / HEADER SCHEDULE / CONNECTION SCHEDULE / FLOOR AND ROOF NOTES.

- PLAN KEY NOTES**
- 12" SQ CMU COLUMN W/(2)#5 FULLY GROUTED
  - LGUM28-3-SDS CONNECTOR BY SIMPSON STRONG TIE w/(6) 3/8"x4" TITEN HD ANCHORS TO MASONRY AND (6) 1/4"x2-1/2" STRONG DRIVE SDS SCREWS

**BUILDER NOTE:**  
TRUSS LAYOUT, CONNECTORS & ENGINEERING BASED ON TRUSSES PROVIDED BY A-1 INDUSTRIES. PROJECT NAME CPSMU4 w/ TRUSS DESIGN DATED 4/24/23 IF THE TRUSS LAYOUT SHOWN DOES NOT MATCH THE TRUSS MANUFACTURERS LAYOUT AND DATE ABOVE

**STOP**  
AND CALL THE ENGINEER OF RECORD PRIOR TO PLACEMENT OF ANY TRUSSES.

SYMBOL	DESIGN DESCRIPTION
	2x INTERIOR BEARING SHEARWALL - SEE BEARING WALL SCHEDULE ON SHEET SN FOR REQUIREMENTS.
	INDICATES BEARING WALL SEE BEARING WOOD BEARING SCHEDULE ON SN
	MASONRY WALL TOP @ 9'-4"
	MASONRY WALL TOP @ 10'-8" ABV. GRADE
	MASONRY WALL TOP @ 10'-8" ABV. GRADE



**B&A Design Studio, Inc.**  
4017 W. 1st Street  
Sanford, FL 32771  
PH: 407 829 8900  
FAX: 407 829 2040  
www.badesignstudios.com



**A-I AMERICAN INSTITUTE OF DESIGN**  
N.C.B.D.O.  
REGISTERED PROFESSIONAL ENGINEER  
FLORIDA LICENSE NO. 9191

**FDS ENGINEERING ASSOCIATES**  
288 Southhall Lane, Suite 200, Maitland, FL 32751  
Tel: 407-829-8900  
Fax: 407-829-2040  
www.fdseng.com


**PARK SQUARE HORIZONS WEST**  
BABCOCK RANCH BLDG. (LOTS 1-4) UNIT

title:  
project no. 2023083  
checked: BA  
drawn: BA  
date: 04-12-23  
scale:  
**S2.2**

NOTE: DRAWINGS ON 11"x17" SHEET WILL BE ONE HALF THE SCALE NOTED



RSH ENGINEERED ROOF PER ASCE 7-16 ROOF DESIGN ALLOWABLE COMPONENTS AND CLADDING WIND PRESSURES AND SUCTIONS FOR MEAN ROOF HEIGHT ≤ 25 ft							
WIND SPEED (ULTIMATE)	150.0 MPH						
WIND SPEED (ALLOWABLE)	116.2 MPH						
EXPOSURE CATEGORY	C						
EFFECTIVE WIND AREA (SQ. FEET)	WIND PRESSURE AND SUCTION (PSF)						
	(+ ) VALUE DENOTES PRESSURE (- ) VALUE DENOTES SUCTION						
AREA	ROOF	1	2e	2n	2r	3	3e
	HIP	-43.90	-60.59	-60.59	-60.59	-60.59	-60.59
10	GABLE	-43.86	-43.86	-69.97	-69.97	-69.97	-90.23
	ROOF SCHEDULING / NAILING ZONES (SHINGLE AND TILE):						
ZONE 1: ASTM F1667 RSR5-01 (8d) NAILS @ 6" O.C. ON EDGE AND 6" O.C. IN FIELD							
ZONE 2e, 2n, 2r: ASTM F1667 RSR5-01 (8d) NAILS @ 4" O.C. ON EDGE AND 4" O.C. IN FIELD							
ZONE 3, 3e, 3r: ASTM F1667 RSR5-01 (8d) NAILS @ 4" O.C. ON EDGE AND 4" O.C. IN FIELD							
ROOF SHEATHING:							
SHINGLE: 3/8" EXP. 1 (2%) or 1/2" EXP. 1 (2%)							
TILE: 1/2" EXP. 1 (2%)							
NOTE:							
1. PER CODE ASTM F1667 RSR5-01 REFERENCE TO 8d (2 3/4" x 0.113") NAILS							
2. WHERE THE SHEATHING THICKNESS IS GREATER THAN 1/2", SHEATHING SHALL BE FASTENED WITH ASTM F1667 RSR5-02 10d (2 1/2" x 0.131") NAILS OR ASTM F1667 RSR5-04 (3" x 120") NAILS							
3. GABLES- DROP GABLE END & (1) ADDITIONAL DROPPED TRUSS 2x4 #2 SYP OUTLOOKER RAFTER W/ BLOCKING @ 16" O.C. IF NO DROPPED GABLE END, ATTACH 2x4 #2 SYP BLOCKING @ 16" O.C. FIRST 4 BAYS WITH (2) 12d NAILS EA. END. ATTACH ROOF SHEATHING TO RAFTERS W/ BLOCKING PER NAILING SCHEDULE.							



SYMBOL	DESIGN DESCRIPTION
	INDICATES BEARING WALL SEE BEARING WOOD BEARING SCHEDULE ON SN - SEE ARCHITECTURAL PLANS FOR WALL WIDTH, 2x4 MINIMUM U.O.N.
	INDICATES PERFORATED SHEAR WALL, SEE ARCHITECTURAL PLANS FOR WALL WIDTH, 2x4 MINIMUM U.O.N.
	INDICATES BUILT UP COLUMN, SEE FRAMING PLAN FOR SIZE, DETAIL WF37/SN FOR PLY ATTACHMENT AND UPLIFT CONNECTION SCHEDULE ON SN FOR CONNECTION TO SLAB
	INDICATES NO BOTTOM CONNECTOR REQUIRED
	INDICATES UPLIFT CONNECTION CONSTRUCTED PER DETAIL UPLIFT CONNECTOR SCHEDULE ON SHEET SN
	INDICATES WINDOW PRESSURE - SEE S0 FOR MORE INFORMATION.
	INDICATES LINTEL PER LINTEL PLAN

**FRAMING NOTES:**

- SEE WIND SPEED CHART ON S0 FOR WINDOW PRESSURES
- AT SECOND FLOOR FOR TYPICAL CORNER FRAMING SEE DETAIL FB06/D3

**GENERAL NOTES:**

- THE FRAMING PLAN SHOWN INDICATES THE "TRUSS SYSTEM" AND IS THE RESPONSIBILITY OF THE TRUSS SYSTEM ENGINEER (DESIGN PROFESSIONAL OF RECORD), THE TRUSS DESIGN ENGINEER (DELEGATED ENGINEER) HAS FINAL, RESPONSIBILITY FOR EACH INDIVIDUAL TRUSS AND TRUSS PROFILE, AND IS TO SUBMIT A FINAL SET OF TRUSS ENGINEERING SIGNED AND SEALED TRUSS DRAWINGS TO DESIGN PROFESSIONAL OF RECORD FOR REVIEW PRIOR TO FABRICATION
- ANY DISCREPANCY OR ERROR IN DIMENSIONS OR NOTES WITH IN THIS PLAN SHALL BE BROUGHT TO THE ATTENTION OF THE DESIGN PROFESSIONAL FOR CLARIFICATION PRIOR TO CONSTRUCTION.
- SEE SHEET SN FOR CONNECTION SCHEDULES AND NOTES: FOUNDATION SCHEDULE / COLUMN SCHEDULE / BEARING WALL SCHEDULE / BEAM SCHEDULE / HEADER SCHEDULE / CONNECTION SCHEDULE / FLOOR AND ROOF NOTES.


**PLAN KEY NOTES**

1 12" SQ CMU COLUMN W/(2)#5 FULLY GROUTED

**BUILDER NOTE:**  
TRUSS LAYOUT, CONNECTORS & ENGINEERING BASED ON TRUSSES PROVIDED BY A-1 INDUSTRIES. PROJECT NAME CP5M4 w/ TRUSS DESIGN DATED 4/24/23 IF THE TRUSS LAYOUT SHOWN DOES NOT MATCH THE TRUSS MANUFACTURERS LAYOUT AND DATE ABOVE


**---STOP---**  
AND CALL THE ENGINEER OF RECORD PRIOR TO PLACEMENT OF ANY TRUSSES.

SYMBOL	DESIGN DESCRIPTION
	2x INTERIOR BEARING SHEARWALL - SEE BEARING WALL SCHEDULE ON SHEET SN FOR REQUIREMENTS.
	INDICATES BEARING WALL SEE BEARING WOOD BEARING SCHEDULE ON SN
	MASONRY WALL TOP @ 9'-4"
	MASONRY WALL TOP @ 10'-8" ABV. GRADE
	MASONRY WALL TOP @ 10'-8" ABV. GRADE



**KEY PLAN**  
**LOW ROOF & FLOOR FRAMING PLAN**  
SCALE: 1/4" = 1'-0"

**B&A Design Studio, Inc.**  
4017 W. 1st Street  
Sanford, FL 32771  
ph: 407 829 8900  
fax: 407 829 2040  
www.badesignstudios.com



**FDS**  
ENGINEERING ASSOCIATES  
288 Southhall Lane, Suite 200, Maitland, FL 32751  
Phone: 407-829-8900  
Fax: 407-829-2040  
www.fdseng.com

**FDS JOB NO.:** \_\_\_\_\_

DATE: November 9, 2023

**PARK SQUARE HORIZONS WEST**  
**BABCOCK RANCH BLDG. (LOTS 1-4) UNIT**


title: \_\_\_\_\_

project no. 2023083  
checked: BA  
drawn: BA  
date: 04-12-23  
scale:

**S2.3**

NOTE: DRAWINGS ON 11"x17" SHEET WILL BE ONE HALF THE SCALE NOTED

<b>RSH</b>	ENGINEERED ROOF PER ASCE 7-16 ROOF DESIGN ALLOWABLE COMPONENTS AND CLADDING WIND PRESSURES AND SUCTIONS FOR MEAN ROOF HEIGHT ≤ 25 ft							
WIND SPEED (ULTIMATE)	150.0 MPH							
WIND SPEED (ALLOWABLE)	116.2 MPH							
EXPOSURE CATEGORY	C							
EFFECTIVE WIND AREA (SQ FEET)	WIND PRESSURE AND SUCTION (PSF) (+) VALUE DENOTES PRESSURE (-) VALUE DENOTES SUCTION							
AREA	ROOF	1	2a	2n	2r	3	3a	3r
10	HIP	-43.90	-60.59	-60.59	-60.59	-60.59		
	GABLE	-43.86	-43.86	-69.97	-69.97	-69.97	-69.97	-90.23
ROOF NAILING SCHEDULE/ NAILING ZONES (SHINGLE AND TILE):								
ZONE 1: ASTM F1667 RSR-01 (8d) NAILS @ 6" O.C. ON EDGE AND 6" O.C. IN FIELD								
ZONE 2a, 2n, 2r: ASTM F1667 RSR-01 (8d) NAILS @ 4" O.C. ON EDGE AND 4" O.C. IN FIELD								
ZONE 3, 3a, 3r: ASTM F1667 RSR-01 (8d) NAILS @ 4" O.C. ON EDGE AND 4" O.C. IN FIELD								
ROOF SHEATHING: SHINGLE: 7/8" EXP. 1 (2% <sub>g</sub> ) or 1 1/2" EXP. 1 (2% <sub>g</sub> )								
TILE: 1 1/2" EXP. 1 (2% <sub>g</sub> )								
NOTE: 1. PER CODE ASTM F1667 RSR-01 REFERENCE TO 8d (2 3/4" x 0.113") NAILS 2. WHERE THE SHEATHING THICKNESS IS GREATER THAN 1/2", SHEATHING SHALL BE FASTENED WITH ASTM F1667 RSR-03 10d (2 1/2" x 0.131") NAILS OR ASTM F1667 RSR-04 (3" x 120") NAILS 3. GABLES- DROP GABLE END & (1) ADDITIONAL DROPPED TRUSS 2x4 #2 SYP OUTLOOKER RAFTER W/ BLOCKING @ 16" O.C. IF NO DROPPED GABLE END. ATTACH 2x4 #2 SYP BLOCKING @ 16" O.C. FIRST 4 BAYS WITH (2) 12d NAILS EA. END. ATTACH ROOF SHEATHING TO RAFTERS W/ BLOCKING PER NAILING SCHEDULE.								
HIP ROOF > 20 TO 27 DEG. [4-12]-[6-12]								
GABLE ROOF > 20 TO 27 DEG. [4-12]-[6-12]								



SYMBOL	DESIGN DESCRIPTION
	INDICATES BEARING WALL SEE BEARING WOOD BEARING SCHEDULE ON SN. SEE ARCHITECTURAL PLANS FOR WALL WIDTH, 2x4 MINIMUM U.O.N.
	INDICATES PERFORATED SHEAR WALL, SEE ARCHITECTURAL PLANS FOR WALL WIDTH, 2x4 MINIMUM U.O.N.
	INDICATES BUILT UP COLUMN, SEE FRAMING PLAN FOR SIZE, DETAIL WF37/SN FOR PLY ATTACHMENT AND UPLIFT CONNECTION SCHEDULE ON SN FOR CONNECTION TO SLAB
	INDICATES NO BOTTOM CONNECTOR REQUIRED
	INDICATES UPLIFT CONNECTION CONSTRUCTED PER DETAIL UPLIFT CONNECTOR SCHEDULE ON SHEET SN
	INDICATES WINDOW PRESSURE - SEE S0 FOR MORE INFORMATION.
	INDICATES LINTEL PER LINTEL PLAN

- FRAMING NOTES:**
- SEE WIND SPEED CHART ON S0 FOR WINDOW PRESSURES
  - AT SECOND FLOOR FOR TYPICAL CORNER FRAMING SEE DETAIL FB06/D3
- GENERAL NOTES:**
- THE FRAMING PLAN SHOWN INDICATES THE "TRUSS SYSTEM" AND IS THE RESPONSIBILITY OF THE TRUSS SYSTEM ENGINEER (DESIGN PROFESSIONAL OF RECORD). THE TRUSS DESIGN ENGINEER (DELEGATED ENGINEER) HAS FINAL, RESPONSIBILITY FOR EACH INDIVIDUAL TRUSS AND TRUSS PROFILE, AND IS TO SUBMIT A FINAL SET OF TRUSS ENGINEERING SIGNED AND SEALED TRUSS DRAWINGS TO DESIGN PROFESSIONAL OF RECORD FOR REVIEW PRIOR TO FABRICATION
  - ANY DISCREPANCY OR ERROR IN DIMENSIONS OR NOTES WITH IN THIS PLAN SHALL BE BROUGHT TO THE ATTENTION OF THE DESIGN PROFESSIONAL FOR CLARIFICATION PRIOR TO CONSTRUCTION.
  - SEE SHEET SN FOR DESIGN SCHEDULES AND NOTES: FOUNDATION SCHEDULE / COLUMN SCHEDULE / BEARING WALL SCHEDULE / BEAM SCHEDULE / HEADER SCHEDULE / CONNECTION SCHEDULE / FLOOR AND ROOF NOTES.

PLAN KEY NOTES	
1	SEE DETAIL WS18/D3 FOR RAISED HEEL TYP. U.N.O.

**BUILDER NOTE:**  
TRUSS LAYOUT, CONNECTORS & ENGINEERING BASED ON TRUSSES PROVIDED BY A-1 INDUSTRIES, PROJECT NAME CPMU4 w/ TRUSS DESIGN DATED 4/24/23 IF THE TRUSS LAYOUT SHOWN DOES NOT MATCH THE TRUSS MANUFACTURERS LAYOUT AND DATE ABOVE

**---STOP---**  
AND CALL THE ENGINEER OF RECORD PRIOR TO PLACEMENT OF ANY TRUSSES.

WALL TYPE	
	2x INTERIOR BEARING SHEARWALL - SEE BEARING WALL SCHEDULE ON SHEET SN FOR REQUIREMENTS.
	INDICATES BEARING WALL SEE BEARING WOOD BEARING SCHEDULE ON SN
	2x WOOD FRAME WALL @ 9'-0"

**KEY PLAN**

**ROOF FRAMING PLAN**

SCALE: 1/4" = 1'-0"

**B&A Design Studio, Inc.**

4017 W. 1st Street  
Sanford, FL 32771  
PH: 407 829 8900  
FAX: 407 829 2040  
www.badesignstudios.com

**FDS**

ENGINEERING ASSOCIATES  
288 Southhall Lane, Suite 200, Maitland, FL 32751  
Phone: 407-829-8900  
Certificate of Authorization No. 9191  
 CARL A. BROWN, PE, FL #45626  
 SCOTT L. LEWIS, PE, FL #27870  
 T. E. November 9, 2023

FDS JOB NO.:

**PARK SQUARE  
HORIZONS WEST  
BARBOCK RANCH BLDG. (LOTS 1-4) UNIT**


title:

project no. 2023083  
checked:  
drawn: BA  
date: 04-12-23  
scale:

**S3.1**

NOTE: DRAWINGS ON 11"x17" SHEET WILL BE ONE HALF THE SCALE NOTED

<b>RSH</b>	ENGINEERED ROOF PER ASCE 7-16 ROOF DESIGN ALLOWABLE COMPONENTS AND CLADDING WIND PRESSURES AND SUCTIONS FOR MEAN ROOF HEIGHT ≤ 25 ft							
WIND SPEED (ULTIMATE)	150.0 MPH							
WIND SPEED (ALLOWABLE)	116.2 MPH							
EXPOSURE CATEGORY	C							
EFFECTIVE WIND AREA (SQ FEET)	WIND PRESSURE AND SUCTION (PSF) (+) VALUE DENOTES PRESSURE (-) VALUE DENOTES SUCTION							
AREA	ROOF	1	2a	2n	2r	3	3a	3r
10	HIP	-43.90	-60.59	-60.59	-60.59	-60.59		
	GABLE	-43.86	-43.86	-69.97	-69.97	-69.97	-69.97	-90.23
ROOF NAILING SCHEDULE / NAILING ZONES (SHINGLE AND TILE):								
ZONE 1: ASTM F1667 RSR-01 (8d) NAILS @ 6" O.C. ON EDGE AND 6" O.C. IN FIELD								
ZONE 2a, 2n, 2r: ASTM F1667 RSR-01 (8d) NAILS @ 4" O.C. ON EDGE AND 4" O.C. IN FIELD								
ZONE 3, 3a, 3r: ASTM F1667 RSR-01 (8d) NAILS @ 4" O.C. ON EDGE AND 4" O.C. IN FIELD								
ROOF SHEATHING:								
SHINGLE: 7/8" EXP. 1 (2 <sup>1/2</sup> ) or 1 1/2" EXP. 1 (2 <sup>1/2</sup> )								
TILE: 1 1/2" EXP. 1 (2 <sup>1/2</sup> )								
NOTE:								
1. PER CODE ASTM F1667 RSR-01 REFERENCE TO 8d (2 1/2" x 0.113") NAILS								
2. WHERE THE SHEATHING THICKNESS IS GREATER THAN 1/2", SHEATHING SHALL BE FASTENED WITH ASTM F1667 RSR-03 10d (2 1/2" x 0.131") NAILS OR ASTM F1667 RSR-04 (3" x 120") NAILS								
3. GABLES - DROP GABLE END & (1) ADDITIONAL DROPPED TRUSS 2x4 #2 SYP OUTLOOKER RAFTER W/ BLOCKING @ 16" O.C. IF NO DROPPED GABLE END. ATTACH 2x4 #2 SYP BLOCKING @ 16" O.C. FIRST 4 BAYS WITH (2) 12d NAILS EA. END. ATTACH ROOF SHEATHING TO RAFTERS W/ BLOCKING PER NAILING SCHEDULE.								
HIP ROOF > 20 TO 27 DEG. [4-12]-[6-12]								
GABLE ROOF > 20 TO 27 DEG. [4-12]-[6-12]								



SYMBOL	DESIGN DESCRIPTION
	INDICATES BEARING WALL SEE BEARING WOOD BEARING SCHEDULE ON SN, SEE ARCHITECTURAL PLANS FOR WALL WIDTH, 2x4 MINIMUM U.O.N.
	INDICATES PERFORATED SHEAR WALL, SEE ARCHITECTURAL PLANS FOR WALL WIDTH, 2x4 MINIMUM U.O.N.
	INDICATES BUILT UP COLUMN, SEE FRAMING PLAN FOR SIZE, DETAIL WF37/SN FOR PLY ATTACHMENT AND UPLIFT CONNECTION SCHEDULE ON SN FOR CONNECTION TO SLAB
	INDICATES NO BOTTOM CONNECTOR REQUIRED
	INDICATES UPLIFT CONNECTION CONSTRUCTED PER DETAIL UPLIFT CONNECTOR SCHEDULE ON SHEET SN
	INDICATES WINDOW PRESSURE - SEE S0 FOR MORE INFORMATION.
	INDICATES LINTEL PER LINTEL PLAN

- FRAMING NOTES:**
- SEE WIND SPEED CHART ON S0 FOR WINDOW PRESSURES
  - AT SECOND FLOOR FOR TYPICAL CORNER FRAMING SEE DETAIL FB06/D3
- GENERAL NOTES:**
- THE FRAMING PLAN SHOWN INDICATES THE "TRUSS SYSTEM" AND IS THE RESPONSIBILITY OF THE TRUSS SYSTEM ENGINEER (DESIGN PROFESSIONAL OF RECORD), THE TRUSS DESIGN ENGINEER (DELEGATED ENGINEER) HAS FINAL, RESPONSIBILITY FOR EACH INDIVIDUAL TRUSS AND TRUSS PROFILE, AND IS TO SUBMIT A FINAL SET OF TRUSS ENGINEERING SIGNED AND SEALED TRUSS DRAWINGS TO DESIGN PROFESSIONAL OF RECORD FOR REVIEW PRIOR TO FABRICATION
  - ANY DISCREPANCY OR ERROR IN DIMENSIONS OR NOTES WITH IN THIS PLAN SHALL BE BROUGHT TO THE ATTENTION OF THE DESIGN PROFESSIONAL FOR CLARIFICATION PRIOR TO CONSTRUCTION.
  - SEE SHEET SN FOR DESIGN SCHEDULES AND NOTES: FOUNDATION SCHEDULE / COLUMN SCHEDULE / BEARING WALL SCHEDULE / BEAM SCHEDULE / HEADER SCHEDULE / CONNECTION SCHEDULE / FLOOR AND ROOF NOTES.

**PLAN KEY NOTES**

1 SEE DETAIL WS18/D3 FOR RAISED HEEL TYP. U.N.O.

**BUILDER NOTE:**

TRUSS LAYOUT, CONNECTORS & ENGINEERING BASED ON TRUSSES PROVIDED BY A-1 INDUSTRIES. PROJECT NAME CPSMU4 w/ TRUSS DESIGN DATED 4/24/23 IF THE TRUSS LAYOUT SHOWN DOES NOT MATCH THE TRUSS MANUFACTURERS LAYOUT AND DATE ABOVE

**---STOP---**

AND CALL THE ENGINEER OF RECORD PRIOR TO PLACEMENT OF ANY TRUSSES.

SYMBOL	DESIGN DESCRIPTION
	2x INTERIOR BEARING SHEARWALL - SEE BEARING WALL SCHEDULE ON SHEET SN FOR REQUIREMENTS.
	INDICATES BEARING WALL SEE BEARING WOOD BEARING SCHEDULE ON SN
	2x WOOD FRAME WALL @ 9'-0"

**KEY PLAN**

**ROOF FRAMING PLAN**

SCALE: 1/4" = 1'-0"

**B&A Design Studio, Inc.**

4017 W. 1st Street  
Sanford, FL 32771  
ph: 407 829 8900  
fax: 407 829 2040  
www.badesignstudios.com

**A-I AMERICAN INSTITUTE OF ARCHITECTS**

Professional Engineer License No. 12154

**FDS ENGINEERING ASSOCIATES**

288 Southhall Lane, Suite 200, Maitland, FL 32751  
Phone: 407-829-8900  
Certificate of Authorization No. 9191

CARL A. BROWN, PE, FL #45626  
 SCOTT L. LEWIS, PE, FL #2750  
 T. E. November 9, 2023

**PARK SQUARE HORIZONS WEST**

BABCOCK RANCH BLDG. (LOTS 1-4) UNIT

title:

project no. 2023083

checked:

drawn: BA

date: 04-12-23

scale:


**S3.2**

NOTE: DRAWINGS ON 11"x17" SHEET WILL BE ONE HALF THE SCALE NOTED




**GENERAL CONCRETE LINTEL SCHEDULE**

APPROVED LINTEL MANUFACTURERS: CASTE-CRETE, QUALITY AND LOTTS.



TYPICAL LINTEL DETAIL



8F12-1B/1T

LINTEL MINIMUM DEPTHS ARE CALLED OUT ON LINTEL PLAN. IF CONTRACTOR INSTALLS A DEEPER LINTEL THAN INDICATED ON THE PLAN, DOING THIS INCREASES THE STRENGTH OF THE LINTEL AND IS APPROVED WITHOUT ENGINEERING LETTER. IF A SMALLER LINTEL IS INSTALLED CONTACT EOR FOR APPROVAL (SEE SHEET L1 FOR LINTEL SCHEDULE).

**LINTEL DESIGNATION SCHEDULE**

MARK	LINTEL DESIGN	MARK	LINTEL DESIGN	MARK	LINTEL DESIGN
A	8RF6-0B/1T	H	8RF30-1B/1T	Q	8RF30-0B/1T
B	8F8-0B/1T	J	8F32-1B/1T	R	8F32-0B/1T
C	8RF14-1B/1T	K	8RF14-0B/1T	S	8F28-1B/1T
D	8F16-1B/1T	L	8F16-0B/1T	T	8F40-1B/1T
E	8F20-1B/1T	M	8F20-0B/1T	U	8F16-2B/2T
F	8RF22-1B/1T	N	8RF22-0B/1T	V	8F12-1B/1T
G	8F24-1B/1T	P	8F24-0B/1T		

**GENERAL INSTALLATION NOTES:**

- PROVIDE FULL MORTAR HEAD AND BED JOINTS.
- SHARE FILLED LINTELS ARE REQUIRED
- INSTALLATION OF LINTEL MUST COMPLY W/ THE ARCHITECTURAL AND STRUCTURAL DRAWINGS
- LINTELS ARE LOCATED MANUFACTURED W/ 5/16" LONG NOTCHES AT THE END TO ACCOMMODATE VERTICAL CELL REINFORCING AND GROUTING.
- ALL LINTELS MEET OR EXCEED L/360 VERTICAL DEFLECTION, EXCEPT LINTELS 17'-4" AND LONGER W/ NOMINAL HEIGHT OF 8" MEET OR EXCEED L/180
- BOTTOM FIELD ADDED REBAR TO BE LOCATED AT THE BOTTOM OF THE LINTEL CAVITY
- 3/4" Ø WIRE STIRRUPS ARE WELDED TO THE BOTTOM STEEL FOR MECHANICAL ANCHORAGE
- CAST-IN-PLACE CONC. MAY BE PROVIDED IN COMPOSITE LINTELS IN LIEU OF CMU SAFE LOAD RATING BASED ON RATIONAL DESIGN ANALYSIS PER ACI 318 AND ACI 530
- FLORIDA APPROVAL NUMBER 158.1
- THE EXTERIOR SURFACE OF LINTELS INSTALLED IN EXTERIOR CONCRETE MASONRY WALLS SHALL HAVE A COATING OF STUCCO APPLIED IN ACCORDANCE WITH ASTM C-926 OR OTHER APPROVED COATING
- LINTELS LOADED SIMULTANEOUSLY W/ VERTICAL (GRAVITY AND UPLIFT) AND HORIZONTAL (LATERAL) LOADS SHOULD BE FOR COMBINE LOADING WITH THE FOLLOWING EQUATIONS:


$$\frac{\text{APPLIED VERTICAL LOAD}}{\text{SAFE VERTICAL LOAD}} + \frac{\text{APPLIED HORIZONTAL LOAD}}{\text{SAFE HORIZONTAL LOAD}} \leq 1.0$$

**GENERAL MATERIAL NOTES:**

- F<sub>o</sub> PRECAST LINTEL = 3500 P.S.I.
- F<sub>c</sub> PRESTRESSED LINTEL = 6000 P.S.I.
- GROUTED PER ASCM C476 F<sub>g</sub> = 3000 P.S.I. W/ MAX 3/4" AGGREGATE AND 8" TO 11" SUMP
- CMU PER ASTM C90 W/ MIN NET AREA COMPRESSION STRENGTH = 2000 P.S.I
- REBAR PER ASTM A615 GRADE 60
- 270 LOW RELAXATION 3/8" WIRE PER ASTM A510
- MORTAR PER ASTM C270 TYPE M OR S

**GENERAL LINTEL NOTES:**

- AREAS OF BLOCK ABV. MASONRY OPENINGS ARE TO BE GROUTED SOLID TO THE BEAM.
- 1-#5 REBAR IN THE BEAM IS TO BE CONT. THROUGH OUT INCLUDING ABV. MASONRY OPENINGS. U.N.O.
- ALL STANDARD LINTELS TO HAVE MIN. 4" BEARING EACH END BASED ON CAST CRETE, LOTTS, AND QUALITY LINTEL SPECS.
- LINTEL MINIMUM DEPTHS ARE CALLED OUT ON LINTEL PLAN. IF CONTRACTOR INSTALLS A DEEPER LINTEL THAN INDICATED ON THE PLAN, DOING THIS INCREASES THE STRENGTH OF THE LINTEL AND IS APPROVED WITHOUT ENGINEERING LETTER. IF A SMALLER LINTEL IS INSTALLED CONTACT EOR FOR APPROVAL.
- (\*) ANY LINTEL DEEPER THAN 32" HAS BEEN VERIFIED TO WORK AS A MIN. 32" FOR THE LOAD CONDITIONS. ANY LINTEL GREATER THAN 32" HAS A GREATER CAPACITY AND THEREFORE IS ADEQUATE FOR THE LOADS
- G.C. TO VERIFY ALL LINTEL DIMENSIONS IN FIELD. DIMENSIONS SHOWN ARE CLEAR SPAN ONLY





MS23 90 DEGREE CORNER DETAIL

SCALE: 3/4" = 1'-0"


**WALL TYPE**

SYMBOL	DESIGN DESCRIPTION
	2x INTERIOR BEARING SHEARWALL - SEE BEARING WALL SCHEDULE ON SHEET SN FOR REQUIREMENTS.
	INDICATES BEARING WALL SEE BEARING WALL SCHEDULE ON SN
	MASONRY WALL TOP @ 9'-4"
	MASONRY WALL TOP @ 10'-8" ABV. GRADE
	MASONRY WALL TOP @ 10'-8" ABV. GRADE




LINTEL PLAN

SCALE: 1/8" = 1'-0"




MS07 DBL LINTEL @ TRANSOM

SCALE: 3/4" = 1'-0"




MS05 TYP. REBAR SPLICE

SCALE: 3/4" = 1'-0"



WF01 MASONRY ARCH FRAMING

SCALE: 3/4" = 1'-0"




MS12 GARAGE DOOR INSTALLATION

SCALE: 3/4" = 1'-0"


SIZE	TAPCONS	SPACING	# ROWS
2 x 4	3/16" X 3"	12" O.C.	1
2 x 6	3/16" X 3"	12" O.C.	2
2 x 8	3/16" X 3"	12" O.C.	2

- NOTES:**
- TAPCONS TO BE 6" FROM END
  - FASTENING TO WINDOW TO BUCK RESPONSIBILITY OF WINDOW MANUFACTURER
  - 1x BUCKS ARE NOT STRUCTURAL AND SHALL BE USED ONLY AS BLOCKING



MS11 MASONRY BUCK INSTALLATION

SCALE: 3/4" = 1'-0"



MS03 MASONRY TO WD BRG WALL

SCALE: 3/4" = 1'-0"

**B&A Design Studio, Inc.**

4017 W. 1st Street  
Sanford, FL 32771  
PH: 407 839 8900  
FAX: 407 839 2040  
www.badesignstudios.com

**AI AMERICAN INSTITUTE OF DESIGN**

**FDS ENGINEERING ASSOCIATES**


288 Southhall Lane, Suite 200, Maitland, FL 32751  
Phone: 407-839-8900  
Certificate of Authorization No. 3191  
SCOTT LEWIS/PE, FE, FL #19726  
CARLA A. BROWN, PE, FL #19726  
DATE: November 9, 2023

**PARK SQUARE HORIZONS WEST BABCOCK RANCH BLDG. (LOTS 1-4) UNIT**


project no. 2023083  
checked: BA  
drawn: BA  
date: 04-12-23  
scale:

**L1**


NOTE: DRAWINGS ON 11"X17" SHEET WILL BE ONE HALF THE SCALE NOTED



**FM21 PARTY WALL FOOTING**  
SCALE: 3/4" = 1'-0"




**FM24 GARAGE PARTY WALL FOOTING**  
SCALE: 3/4" = 1'-0"



**TYP. LANDING FRAMING SECTION**

**TYP. BASE OF STAIR FRAMING SECTION**



**SD02 GENERAL STAIR SECTIONS & PLAN**  
SCALE: 3/4" = 1'-0"

# CAST CRETE OR QUALITY/ LOTTS LINTEL LOAD SPECIFICATIONS

**SAFE GRAVITY LOADS FOR 8" PRECAST & PRESTRESSED U-LINTELS**

LENG.T.H	TYPE	SAFE LOAD - POUNDS PER LINEAR FOOT														
		8F8-0B	8F12-0B	8F16-0B	8F20-0B	8F24-0B	8F28-0B	8F32-0B	8F8-1B	8F12-1B	8F16-1B	8F20-1B				
2'-10" (34")	PRECAST	2231	3069	4605	6113	7547	8974	10394	11809	3069	4605	6113	7547	8974	10394	11809
3'-6" (42")	PRECAST	2231	3069	3719	5163	6607	8054	9502	10951	3069	4605	6113	7547	8974	10394	11809
4'-0" (48")	PRECAST	1966	2561	2751	3820	4890	5961	7034	8107	2561	2751	3820	4890	5961	7034	8107
4'-6" (54")	PRECAST	1599	1969	2110	2931	3753	4576	5400	6224	1969	2110	2931	3753	4576	5400	6224
5'-4" (64")	PRECAST	1217	1349	1438	1999	2560	3123	3686	4249	1349	1438	1999	2560	3123	3686	4249
5'-10" (70")	PRECAST	1062	1105	1173	1631	2090	2549	3009	3470	1105	1173	1631	2090	2549	3009	3470
6'-6" (78")	PRECAST	908	1238	1238	1737	2236	2735	3234	3733	1238	1238	1737	2236	2735	3234	3733
7'-6" (90")	PRECAST	743	1011	1011	1429	1847	2265	2683	3101	1011	1011	1429	1847	2265	2683	3101
9'-4" (112")	PRECAST	554	699	699	1160	1625	2090	2555	3020	699	699	1160	1625	2090	2555	3020
10'-6" (126")	PRECAST	475	535	535	890	1247	1603	1959	2315	535	535	890	1247	1603	1959	2315
11'-4" (136")	PRECAST	362	582	582	945	1366	1846	2326	2806	582	582	945	1366	1846	2326	2806
12'-0" (144")	PRECAST	337	540	540	873	1254	1684	2114	2544	540	540	873	1254	1684	2114	2544
13'-4" (160")	PRECAST	296	471	471	755	1075	1428	1838	2316	471	471	755	1075	1428	1838	2316
14'-0" (168")	PRECAST	279	442	442	706	1002	1326	1697	2127	442	442	706	1002	1326	1697	2127
14'-8" (176")	PRESTRESSED	N.R.	NR	NR	NR	NR	NR	NR	NR	NR	NR	NR	NR	NR	NR	NR
15'-4" (184")	PRESTRESSED	N.R.	458	458	783	1370	1902	2445	2917	458	458	783	1370	1902	2445	2917
17'-4" (208")	PRESTRESSED	N.R.	412	412	710	1250	1733	2258	2730	412	412	710	1250	1733	2258	2730
19'-4" (232")	PRESTRESSED	N.R.	300	300	548	950	1326	1849	2347	300	300	548	950	1326	1849	2347
21'-4" (256")	PRESTRESSED	N.R.	235	235	420	750	1037	1428	1820	235	235	420	750	1037	1428	1820
22'-0" (264")	PRESTRESSED	N.R.	180	180	340	598	845	1114	1468	180	180	340	598	845	1114	1468
24'-0" (288")	PRESTRESSED	N.R.	165	165	315	550	784	1047	1399	165	165	315	550	784	1047	1399
24'-0" (288")	PRESTRESSED	N.R.	129	129	250	450	654	884	1092	129	129	250	450	654	884	1092

(#) THE NUMBERS IN PARENTHESIS ARE PERCENT REDUCTIONS FOR GR40 FIELD ADDED REBAR.

## SAFE UPLIFT LOADS FOR 8" PRECAST & PRESTRESSED U-LINTELS

LENG.T.H	TYPE	SAFE LOAD - POUNDS PER LINEAR FOOT													
		8F8-1T	8F12-1T	8F16-1T	8F20-1T	8F24-1T	8F28-1T	8F32-1T	8F8-2T	8F12-2T	8F16-2T	8F20-2T			
2'-10" (34")	PRECAST	1972	3173	4460	5747	7034	8321	9608	1972	3173	4460	5747	7034	8321	9608
3'-6" (42")	PRECAST	1569	2524	3547	4569	5591	6613	7636	1569	2524	3547	4569	5591	6613	7636
4'-0" (48")	PRECAST	1363	2192	3079	3966	4853	5740	6627	1363	2192	3079	3966	4853	5740	6627
4'-6" (54")	PRECAST	1207	1940	2724	3508	4292	5077	5861	1207	1940	2724	3508	4292	5077	5861
5'-4" (64")	PRECAST	1016	1632	2290	2949	3607	4265	4924	1016	1632	2290	2949	3607	4265	4924
5'-10" (70")	PRECAST	929	1492	2093	2694	3295	3897	4498	929	1492	2093	2694	3295	3897	4498
6'-6" (78")	PRECAST	835	1340	1880	2419	2959	3498	4038	835	1340	1880	2419	2959	3498	4038
7'-6" (90")	PRECAST	727	1166	1634	2102	2571	3039	3508	727	1166	1634	2102	2571	3039	3508
9'-4" (112")	PRECAST	591	851	1185	1520	1855	2190	2525	591	851	1185	1520	1855	2190	2525
10'-6" (126")	PRECAST	530	727	1021	1315	1609	1903	2197	530	727	1021	1315	1609	1903	2197
11'-4" (136")	PRECAST	494	648	896	1144	1392	1640	1888	494	648	896	1144	1392	1640	1888
12'-0" (144")	PRECAST	470	543	723	936	1151	1366	1582	470	543	723	936	1151	1366	1582
13'-4" (160")	PRECAST	428	485	659	873	1087	1301	1515	428	485	659	873	1087	1301	1515
14'-0" (168")	PRECAST	384	410	546	732	918	1104	1290	384	410	546	732	918	1104	1290
14'-8" (176")	PRESTRESSED	246	246	390	555	720	885	1050	246	246	390	555	720	885	1050
15'-4" (184")	PRESTRESSED	230	230	364	509	674	839	1004	230	230	364	509	674	839	1004
17'-4" (208")	PRESTRESSED	187	187	285	383	517	651	785	187	187	285	383	517	651	785
19'-4" (232")	PRESTRESSED	166	166	264	352	476	600	724	166	166	264	352	476	600	724
21'-4" (256")	PRESTRESSED	142	142	230	318	422	526	630	142	142	230	318	422	526	630
22'-0" (264")	PRESTRESSED	137	137	225	313	417	521	625	137	137	225	313	417	521	625
24'-0" (288")	PRESTRESSED	124	124	210	298	392	486	580	124	124	210	298	392	486	580

(#) THE NUMBERS IN PARENTHESIS ARE PERCENT REDUCTIONS FOR GR40 FIELD ADDED REBAR.

**B&A Design Studio, Inc.**  
4017 W. 1st Street  
Sanford, FL 32771  
ph: 407 829 8900  
fax: 407 829 2040  
www.badesignstudios.com

**N.C.B.D.C.**  
**A.I.A.**  
**AMERICAN INSTITUTE OF ARCHITECTS**

**FDS**  
288 Southhall Lane, Suite 200, Maitland, FL 32751  
Tel: 407-829-8900  
Fax: 407-829-2040  
www.fdseng.com

**PARK SQUARE HORIZONS WEST**  
BABCOCK RANCH BLDG. (LOTS 1-4) UNIT

title:  
project no. 2023083  
checked:  
drawn: BA  
date: 04-12-23  
scale:  
**L2**

NOTE: DRAWINGS ON 11"x17" SHEET WILL BE ONE HALF THE SCALE NOTED


MARK	SIZE	DEPTH	REINFORCING	GRAVITY CAP. [lbs]
F1.5	1'-6" x 1'-6"	1'-0"	(2) #5 E.W. BOT.	3500
F2.0	4'-0" x 2'-0"	1'-0"	(3) #5 E.W. BOT.	7200
F2.5	2'-6" x 2'-6"	1'-0"	(3) #5 E.W. BOT.	11000
F3.0	3'-0" x 3'-0"	1'-0"	(4) #5 E.W. BOT.	15600
F3.5	3'-6" x 3'-6"	1'-0"	(4) #5 E.W. BOT.	21500
F4.0	4'-0" x 4'-0"	1'-0"	(5) #5 E.W. BOT.	28000
F4.5	4'-6" x 4'-6"	1'-4"	(5) #5 E.W. BOT.	34500
F5.0	5'-0" x 5'-0"	1'-4"	(5) #5 E.W. BOT.	42500
F6.0	6'-0" x 6'-0"	1'-6"	(6) #5 E.W. BOT.	

**FOUNDATION DEPTH NOTE:**  
 • INTERIOR PAD DEPTHS AS LISTED IN THE SCHEDULE ARE THE TOTAL DEPTH AND MEASURED FROM THE TOP OF THE SLAB.  
 • EXTERIOR PAD DEPTHS AS LISTED IN THE SCHEDULE ARE TOTAL DEPTH WITH THE BOTTOM OF THE FOOTING TO MATCH THE BOTTOM OF THE CONTINUOUS MONOLITHIC POUR WHICH RUNS THROUGH IT.





**GENERAL FOUNDATION NOTES:**  
 1. PROVIDE MIN. 6 MIL. APPROVED VAPOUR BARRIER. ALL JOINTS TO BE LAPPED MIN. 6" AND SEALED.  
 2. #2 2500 PSI CONC. SLAB WITH W1.4x1/4 OVER 6 MIL. VISQUEEN VAPOUR BARRIER & TREATED FOR TERMITES.  
 3. GC/BUILDER, SEE ARCH PLANS FOR FOUR OPENING LOCATIONS AND ADDITIONAL INFORMATION REQUIRED FOR DOOR/WINDOW.  
 4. INSTALLATION ALONG W/ DIMENSIONS NOT SHOWN ON FOUNDATION CONSULT W/ MANUFACTURER SPECIFICATIONS PRIOR TO POURING OR RECESSING DOWEL SILLS OR SLIDING GLASS DOOR SILLS.  
 5. NO WOOD STAKES PERMITTED IN FOUNDATION.  
 6. PENDING SITE CONDITIONS, FOUNDATION MAY HAVE TO BE STEPPED DOWN. SEE **FM18D1** FOR ADDITIONAL INFORMATION. G.C. TO DETERMINE STEP LOCATIONS, IF REQUIRED.  
 7. STEEL BENDS AND LAP SPICE SEE **FM18D1** AND **FM19D1**.  
 8. ALL EQUIPMENT AND/OR APPLIANCES HAVING AN IGNITION SOURCE SHALL BE ELEVATED A MIN OF 18". CONTRACTOR TO PROVIDE SUCH PLATFORM W/ EITHER MASONRY OR WOOD CONSTRUCTION.  
 9. ASSUMED ALLOWABLE SOIL BEARING PRESSURE AFTER COMPACTION: 2000 PSF. SEE SOIL REPORT AND SPECIFICATIONS FOR COMPACTION REQUIREMENTS. IF SOIL CONDITIONS ON THE PROJECT DO NOT MEET OR EXCEED THE CAPACITY, THE GENERAL CONTRACTOR SHALL CONTACT THE ENGINEER PRIOR TO FOUNDATION POUR FOR VERIFICATION OF FOUNDATION DESIGN. SOIL TO BE FREE OF ORGANIC MATERIAL AND COHESIVE SOILS, COMPACTED IN 12" LIFTS TO AT LEAST 95% OF MAX. DRY DENSITY AS DETERMINED BY ASTM D 1557 (MODIFIED PROCTOR).  
 10. R.403 1/4 MINIMUM DEPTH EXTERIOR FOOTINGS SHALL BE PLACED NOT LESS THAN 12 INCHES (305mm) BELOW THE FINISHED GRADE OF GROUND SURFACE.

MARK	COLUMN SIZE	FIRST FLOOR BASE CONNECTIONS. SEE PLAN FOR SECOND FLOOR CONNECTIONS	UPLIFT (lb)
C1	(3) 2x #2 SPF	(4)12d TOENAILS	NO UPLIFT
C2	(3) 2x #2 SPF	DT22 W/ 1/2" ATR & (8) 1/4" x 1 1/2" SDS SCREWS	1835
C3	(3) 2x #2 SPF	(4)12d TOENAILS	NO UPLIFT
C4	(3) 2x #2 SPF	DT22 W/ 1/2" ATR & (8) 1/4" x 1 1/2" SDS SCREWS	1835
C5	4x4 P.T.#2 SYP POST	ABU44 W/ 3/4" ATR & (12) 16d NAILS FIRST/SECOND FLOOR CONN.	G = 6665 U = 1782
C6	6x6 P.T.#2 SYP POST	ABU66 W/ 3/4" ATR & (12) 16d NAILS FIRST/SECOND FLOOR CONN.	G = 12000 U = 2070
C7	8x8 P.T.#2 SYP POST	ABU88 W/ 3/4" ATR & (18) 16d NAILS FIRST/SECOND FLOOR CONN.	G = 24335 U = 2088
C8	3.5" x 3.5" P.L. 1.8E Fp=2400 PSI	HDU5-SDS2.5 W/ 3/4" ATR AND (14) 1/2"x2 1/2" SDS WOOD SCREWS	5080
C9	3.5" x 5.25" P.L. 1.8E Fp=2400 PSI	HDU5-SDS2.5 W/ 3/4" ATR AND (14) 1/2"x2 1/2" SDS WOOD SCREWS	5080
C10	3.5" x 7" P.L. 1.8E Fp=2400 PSI	HDU8-SDS2.5 W/ 3/4" ATR AND (20) 1/2"x2 1/2" SDS WOOD SCREWS	6372
C11	5.25" x 5.25" P.L. 1.8E Fp=2400 PSI	HDU8-SDS2.5 W/ 3/4" ATR AND (20) 1/2"x2 1/2" SDS WOOD SCREWS	7082





**GENERAL COLUMN NOTES:**  
 1. ALL STRUCTURAL LUMBER TO BE SYP#2 OR SYP#2 UNO ON PLAN.  
 2. MINIMUM BOLT EMBEDMENT: 5" EMBEDMENT FOR 1/2" ATR. 6" EMBEDMENT FOR 3/4" ATR. 8" EMBEDMENT FOR 1" ATR.  
 3. P.L. COL. TO BRG DIRECTLY ON FOUNDATION. CUT BASE PLATE AS REQ. G.C. TO PROVIDE MOISTURE BARRIER.  
 4. IF COL. IS CALLED OUT ON 2ND FLOOR, THE BASE CONNECTION IS NOT REQ'D. SEE PLANS FOR BASE CONNECTION.  
 5. VALUES HAVE BEEN REDUCED FOR NARROW FACE APPLICATION. CONNECTIONS SHALL BE INSTALLED ON NARROW OR WIDE FACE PER SIMPSON TC-SCCLM













MARK	STUD SPACING	CONNECTION & FASTENERS	LUMBER SPECIES	UPLIFT CAP. [lb]
BW1	16"	(2)16d TOENAILS (3) 12d TOENAILS OR (2) TOENAILS	#2 SPF	NO UPLIFT
BW2	16"	SP2 w/ (6)10d NAILS SP1 w/ (6) 10d NAILS & ANCHOR BOLTS	#2 SPF	402
BW3	16"	(2) SP2 w/ (6)10d NAILS (2) SP1 w/ (6) 10d NAILS & ANCHOR BOLTS	#2 SPF	804
BW4	16"	(2)16d TOENAILS (3) 12d TOENAILS OR (2) TOENAILS	#2 SYP	NO UPLIFT
BW5	16"	SP2 w/ (6)10d NAILS SP1 w/ (6) 10d NAILS & ANCHOR BOLTS	#2 SYP	439
BW6	16"	(2) SP2 w/ (6)10d NAILS (2) SP1 w/ (6) 10d NAILS & ANCHOR BOLTS	#2 SYP	878
BW7	12"	(2)16d TOENAILS (3) 12d TOENAILS OR (2) TOENAILS	#2 SPF	NO UPLIFT
BW8	12"	SP2 w/ (6)10d NAILS SP1 w/ (6) 10d NAILS & ANCHOR BOLTS	#2 SPF	535
BW9	12"	(2) SP2 w/ (6)10d NAILS (2) SP1 w/ (6) 10d NAILS & ANCHOR BOLTS	#2 SYP	1070
BW10	12"	(2)16d TOENAILS (3) 12d TOENAILS OR (2) TOENAILS	#2 SYP	NO UPLIFT
BW11	12"	SP2 w/ (6)10d NAILS SP1 w/ (6) 10d NAILS & ANCHOR BOLTS	#2 SYP	585
BW12	12"	(2) SP2 w/ (6)10d NAILS (2) SP1 w/ (6) 10d NAILS & ANCHOR BOLTS	#2 SYP	1170



MARK	HEADER SIZE	HEADER NOTES
H1	(2) 2x6 #2 SYP w/ 7/16\"/>	
H2	(2) 2x8 #2 SYP w/ 7/16\"/>	
H3	(2) 2x10 #2 SYP w/ 7/16\"/>	
H4	(2) 2x12 #2 SYP w/ 7/16\"/>	
H5	(2) 1 3/4\"/>	
H6	(2) 1 3/4\"/>	
H7	(2) 2x10 #2 SYP w/ 1\"/>	
H8	(2) 2x6 #2 SYP w/ 7/16\"/>	



MARK	TYPE	CONNECTOR & FASTENERS	SYP	SPF	CONNECTOR & FASTENERS	SYP	SPF
A	FRAME TO MASONRY	HETA16 w/ (9)10d x 1 1/2\"/>					
B	FRAME TO FRAME	H2.5A w/ (10)8d x 2-1/2\"/>					
C	FRAME TO FRAME	H10A w/ (18)10d x 1 1/2\"/>					
D	FRAME TO FRAME	MTS12 w/ (16)10d x 1 1/2\"/>					
E	FRAME TO MASONRY	MGT1 w/ (2)10d NAILS AND 5/8\"/>					
F	FRAME TO FRAME	HTS20 w/ (16)10d x 1 1/2\"/>					
G	FRAME TO MASONRY	HTS20 w/ (16)10d NAILS AND (2) 5/8\"/>					
H	FRAME TO MASONRY	FTGR w/ (18) 1/4\"/>					
J2	FRAME TO MASONRY / FRAME	(2) LGT2 w/ (32) 16d SINKERS & (14) 1/4\"/>					
J3	FRAME TO MASONRY / FRAME	(2) LGT3 w/ (32) 16d SINKERS & (14) 1/4\"/>					
K	BEAM TO BEAM	HU410 OPT HU410 w/ (18) 16d & (10) 19d NAILS	G4250	U81795	G42800	U81635	
L	BEAM TO MASONRY	HU410 OPT HU410 w/ (18) TITEN TURBO 1/4\"/>					
M	FRAME TO MASONRY	HTS16 w/ (8)10d NAILS AND (4) 1/4\"/>					
N	FRAME TO MASONRY	HTS20 w/ (10)10d NAILS AND (4) 1/4\"/>					
P	FRAME TO MASONRY	H105 w/ (8) 8d x 1 1/2\"/>					
Q	FRAME TO MASONRY	DT12 w/ (8) 8d x 1 1/2\"/>					
R	FRAME TO MASONRY	HTTS w/ (26) 10d x 1 1/2\"/>					
S	FRAME TO MASONRY	HTTA w/ (18) 16d x 2 1/2\"/>					
T	FRAME TO FRAME	H105 w/ (24) 10d x 1 1/2\"/>					
U	FRAME TO MASONRY	HMMKT w/ (8) 1/4\"/>					
V	FRAME TO MASONRY	VGT w/ (16) 1/4\"/>					
W	FRAME TO MASONRY	VGT w/ (16) 1/4\"/>					
X	FRAME TO FRAME	VGT w/ (16) 1/4\"/>					
Y	FRAME TO FRAME	HTTS w/ (26) 10d x 1 1/2\"/>					



**B&A Design Studio, Inc.**  
 4017 W. 1st Street  
 Sanford, FL 32971  
 PH: 407 833 8900  
 FAX: 407 833 2040  
 www.badesignstudios.com

**ALL AMERICAN**  
 258 Southlake Lane, Suite 200, Melbourne, FL 32951  
 (407) 486-8888  
 Office of Authorization No. 5967  
 CARLA A. BROWN, PE, FL #4626  
 SCOTT L. EDWARDS, PE, FL #27820  
 T. E. November 9, 2023  
 THE SEAL OF THE PROFESSIONAL ENGINEER IS THE PROPERTY OF THE STATE BOARD OF PROFESSIONAL ENGINEERS AND ARCHITECTS.


**FDS**  
 258 Southlake Lane, Suite 200, Melbourne, FL 32951  
 (407) 486-8888  
 Office of Authorization No. 5967  
 CARLA A. BROWN, PE, FL #4626  
 SCOTT L. EDWARDS, PE, FL #27820  
 T. E. November 9, 2023  
 THE SEAL OF THE PROFESSIONAL ENGINEER IS THE PROPERTY OF THE STATE BOARD OF PROFESSIONAL ENGINEERS AND ARCHITECTS.

**PARK SQUARE HORIZONS WEST**  
 BABCOCK RANCH BLDG. (LOTS 1-4 UNIT)


title:  
 project no. 2023083  
 checked: BA  
 drawn: BA  
 date: 04-12-23  
 scale:  
**SN**

NOTE: DRAWINGS ON 11"x17" SHEET WILL BE ONE HALF THE SCALE NOTED


The structural design of this building is in accordance with the FLORIDA BUILDING CODE 7TH EDITION (2020) RESIDENTIAL and is certified as such.




**FM01** SINGLE STORY FTG  
SCALE: 3/4" = 1'-0"




**FM02** SECTION @ GARAGE  
SCALE: 3/4" = 1'-0"




**FM03** THICKENED EDGE  
SCALE: 3/4" = 1'-0"




**FM08** 2-STORY FOOTING  
SCALE: 3/4" = 1'-0"




**FM09** SECTION @ GARAGE DOOR  
SCALE: 3/4" = 1'-0"




**FM10** INTERIOR BEARING WALL  
SCALE: 3/4" = 1'-0"




**FM11** STEP DOWN BEARING  
SCALE: 3/4" = 1'-0"




**FM12** STEP DOWN NON-BEARING  
SCALE: 3/4" = 1'-0"




**FM14** SECTION @ SHOWER  
SCALE: 3/4" = 1'-0"




**FM15** EXTERIOR BEARING @ RECESS  
SCALE: 3/4" = 1'-0"




**FM20** CONTROL JOINT  
SCALE: 3/4" = 1'-0"




**FM19** TYP. CORNER BAR DETAIL  
SCALE: 3/4" = 1'-0"



**FM18** TYP. STEP FOOTING DETAIL  
SCALE: 3/4" = 1'-0"




**FM22** PORCH STEP  
SCALE: 3/4" = 1'-0"




MASONRY CONTROL JOINT

SITE WALL SCHEDULE				
SITE WALL HEIGHT (ft)	FOOTING SIZE		NUMBER/SIZE OF BARS	MAXIMUM DOWEL SPACING
	WIDTH	DEPTH		
0'-0" - 2'-8"	2'-0"	1'-0"	w/ (3) #5 CONT.	#5 @ 72" O.C.
>2'-8" - 5'-0"	3'-0"	1'-0"	w/ (3) #5 CONT.	#5 @ 48" O.C.
>5'-0" - 7'-0"	3'-4"	1'-0"	w/ (5) #5 CONT.	#5 @ 24" O.C.
>7'-0" - 8'-0"	4'-0"	1'-4"	w/ (5) #5 CONT. & #5 @ 32" O.C. TRANSV.	#6 @ 24" O.C.



**FS12** SITE WALL DETAIL  
SCALE: 3/4" = 1'-0"

- CONTROL JOINTS TO BE LOCATED AT 20' O.C. MAX AND @ ALL CHANGES IN WALL WIDTHS
- G.C TO COORDINATE ALL UTILITIES IN EASEMENT



**FM23** FOUNDATION PENETRATIONS, TYPICAL  
SCALE: 3/4" = 1'-0"

**B&A Design Studio, Inc.**  
4017 W. 1st Street  
Sanford, FL 32771  
PH: 407 829 8900  
FAX: 407 829 2040  
www.badesignstudios.com

**A.I. AMERICAN INSTITUTE OF ARCHITECTS**  
N.C.B.D.O.  
REGISTERED ARCHITECT  
FLORIDA ARCHITECTURAL BOARD  
No. 91961


**FDS ENGINEERING ASSOCIATES**  
288 Southall Lane, Suite 200, Maitland, FL 32751  
Tel: 407-829-8900  
Fax: 407-829-2040  
www.fdseng.com  
Professional Seal: CARLA A. BROWN, PE, FL # 45626  
SCOTT L. LEWIS, PE, FL # 27970  
DATE: November 9, 2023  
PROJECT: PARK SQUARE HORIZONS WEST BABCOCK RANCH BLDG. (LOTS 1-4) UNIT 1

PARK SQUARE  
HORIZONS WEST  
BABCOCK RANCH BLDG. (LOTS 1-4) UNIT 1


title:  
project no. 2023083  
checked: BA  
drawn: BA  
date: 04-12-23  
scale:

**D1**


NOTE: DRAWINGS ON 11"x17" SHEET WILL BE ONE HALF THE SCALE NOTED




**TB01** CROSS BRACING, TYP.  
SCALE: 3/4" = 1'-0"




**TB02** CROSS BRACING TYPICAL  
SCALE: N.T.S.




**TB03** HIP/RIDGE BLOCKING  
SCALE: 3/4" = 1'-0"




**TB04** TRUSS BRACING OVER LAP  
SCALE: 3/4" = 1'-0"




**WF21** KNEE WALL @ ENTRY (OPTION)  
SCALE: 3/4" = 1'-0"




**TB05** REQUIRED MIN. PERMANENT TRUSS BRACING PLAN  
SCALE: N.T.S.




**GE01** GABLE END BRACE  
SCALE: 3/4" = 1'-0"




**TB14** NON-BEARING EXTERIOR WALL  
SCALE: 3/4" = 1'-0"




**WS01** 1-STORY WALL SECTION  
SCALE: 3/4" = 1'-0"




**TB06** BLOCKING/CONV. FRAME DETAILS  
SCALE: 1/2" = 1'-0"




**CD12** PORCH COLUMN FRAMING  
SCALE: 3/4" = 1'-0"




**WF27** KNEEWALL @ ENTRY  
SCALE: 3/4" = 1'-0"



**SF01** STRUCTURAL SOFFIT  
SCALE: 3/4" = 1'-0"



**SR01** SHED ROOF CONNECTION  
SCALE: 3/4" = 1'-0"



**PS18** TYPICAL POCKET S.G.D. FRAMING  
SCALE: 3/4" = 1'-0"

**B&A Design Studio, Inc.**  
4017 W. 1st Street  
Sanford, FL 32771  
PH: 407 820 8900  
FX: 407 820 2040  
www.badesignstudios.com




















**A.I. AMERICAN INSTITUTE OF DESIGN**  
N.C.B.D.O. REGISTERED ARCHITECT

**FDS ENGINEERING ASSOCIATES**  
288 Southhall Lane, Suite 200, Maitland, FL 32751  
SCOTT L. EDWARDS, P.E., F.L.S. 6226  
SCOTT L. EDWARDS, P.E., F.L.S. 6226  
TELE: November 9, 2023

**PARK SQUARE HORIZONS WEST**  
BABCOCK RANCH BLDG. (LOTS 1-4) UNIT 14

project no. 2023083  
checked: BA  
drawn: BA  
date: 04-12-23  
scale:

NOTE: DRAWINGS ON 11"x17" SHEET WILL BE ONE HALF THE SCALE NOTED









**B&A Design Studio, Inc.**  
 4017 W. 1st Street  
 Sanford, FL 32771  
 PH: 407 820 8900  
 FAX: 407 820 2040  
 www.badesignstudios.com

**FDS**  
 ENGINEERING ASSOCIATES  
 298 Southhall Lane, Suite 200, Maitland, FL 32751  
 (407) 820-8900  
 Certificate of Authorization No. 9161  
 CARL A. BROWN, P.E. FL #45626  
 SCOTT L. BROWN, P.E. FL #29790  
 DATE: November 9, 2023  
 PROJECT NO: \_\_\_\_\_

**PARK SQUARE  
 HORIZONS WEST  
 BABCOCK RANCH BLDG. (LOTS 1-4) UNIT \_\_\_\_\_**

title: \_\_\_\_\_  
 project no. 2023083  
 checked: BA  
 drawn: BA  
 date: 04-12-23  
 scale: \_\_\_\_\_  
**D3**

NOTE: DRAWINGS ON 11"x17" SHEET WILL BE ONE HALF THE SCALE NOTED



B&A Design Studio, Inc. 4017 W. 1st Street Sanford, FL 32771 ph: 407 829 8900 fax: 407 829 2040 www.badesignstudios.com

N.C.B.D.O. A.I. AMERICAN INSTITUTE OF DESIGN PROFESSIONALS

FDS ENGINEERING ASSOCIATES 288 Southhall Lane, Suite 200, Maitland, FL 32751 Phone: 407-829-8900 Certificate of Authorization No. 9191

[ ] CARL A. BROWN, PE, FL #45626 [ ] SCOTT LEWOWSKI, PE, FL #2750 [ ] DATE: November 9, 2023

FDS JOB NO.:

PARK SQUARE HORIZONS WEST BABCOCK RANCH BLDG. (LOTS 1-4) UNIT


title:

project no. 2023083 checked: BA drawn: BA date: 04-12-23 scale:


**D4**

COPYRIGHT © 2020 ASHTON WOODS RESERVES COPYRIGHT & OTHER RIGHTS RESTRICTING THESE DOCUMENTS TO THE ORIGINAL SITE OR PURPOSE FOR WHICH THEY WERE PREPARED. REPRODUCTIONS, CHANGES OR ASSIGNMENTS ARE PROHIBITED.


NOTE: DRAWINGS ON 11"x17" SHEET WILL BE ONE HALF THE SCALE NOTED




**4** TYPICAL 2 STORY 2-HR. RATED PARTY WALL AT ROOF SYSTEM  
SCALE: 3/4" = 1'-0"




**3** TYPICAL 2 STORY 2-HR. RATED PARTY WALL AT FLOOR SYSTEM  
SCALE: 1" = 1'-0"




**4C** 1-HR RATED OVERHANG DETL.  
PER FBCR 2020 R302.1 WHEN APPLICABLE  
SCALE: 3/4" = 1'-0"




**4D** 1-HR RATED STEPPED ROOF DETL.  
SCALE: 3/4" = 1'-0"




**4F** SOFFIT AT FRAME WALL  
SCALE: 3/4" = 1'-0"



**4A** TYPICAL 2-HR. RATED PARTY WALL AT GARAGE ROOF SYSTEM  
SCALE: 3/4" = 1'-0"



**2** TYPICAL 2 STORY 2-HR. RATED PARTY WALL AT FOUNDATION  
SCALE: 1" = 1'-0"



**1** TYPICAL 2 STORY 2-HR. RATED PARTY WALL ASSEMBLY  
SCALE: 1/2" = 1'-0"

**B&A Design Studio, Inc.**  
4017 W. 1st Street  
Sanford, FL 32771  
ph: 407.829.8900  
fax: 407.829.2040  
www.badesignstudios.com

**FDS**  
ENGINEERING ASSOCIATES  
288 Southhall Lane, Suite 200, Maitland, FL 32751  
Professional Engineer No. 9191  
Certificate of Authorization No. 9191  
CARL A. BROWN, PE, FL # 6526  
SCOTT LEWIS/ENR, PE, FL # 28790  
DATE: November 9, 2023  
PROJECT NO. 2023083

**PARK SQUARE  
HORIZONS WEST  
BABCOCK RANCH BLDG. (LOTS 1-4) UNIT**

title:  
project no. 2023083  
checked: BA  
drawn: BA  
date: 04-12-23  
scale:  
**FP**  
STRUCTURAL

NOTE: DRAWINGS ON 11"x17" SHEET WILL BE ONE HALF THE SCALE NOTED